

JONI MULTI 100L

The Joni jacketed kettle Multi model 100L is a convenient and simple to use classic non-mixing kettle with an electric tilt function.

Incredible time and labour saver in process and production cooking for optimal temperature control, safety and efficiency.
Joni kettles are unique in their seamless construction. One piece welded high grade stainless steel with no manufacturing joins inside the bowl. This maximises efficiency, hygiene, ease of cleaning and overall life expectancy.
Supplied as standard with AutoTemp 32 control
Winning Features

Electric tilt function
Electric water flow meter
Quick and easy to use and empty
Unheated, insulated top
Min 400mm tilt height
Easy to clean
Seamless construction
Several kettles can be linked together
Infinitely variable heating

Auto-filling steam generator

Link the Multi with MultiMix, Opti and OptiMix for kitchens seeking labour saving and user-friendly solutions.
Kettles are supplied as standard with a lightweight tight-closing lid for added safety and efficiency. Ergonomic, quick and easy to empty and maintain. The Multi Joni jacketed kettles are available in multiple litre capacities from 40L through to 300L and can be supplied as a steam or electric heated kettle.
Multi 100L Standard AutoTemp 32 control features

Electric tilt with TiltBack function
Digital control and display of inner kettle temperature
Electronic control of jacket temperature
Clock and timer
Cold water tap for filling
Digital controls with infinitely variable temperature
Pressure or overheating indicator light
Automatic steam water level control

Multi kettles can be fitted with optional additional functions and a range of accessories.

(Multi100L)

SKU
Multi100L

Type
Joni Multi

Category
Kettle

Type
Multi

Construction
Stainless steel

Working pressure
1.0 bar

Max. steam temperature
120° C

Max, temperature on outside of kettle bowl
Less 40° C

Working height
900 mm

Max. cooking capacity
100 litres

Stirrer speed rpm min-max
NA

Weight (kg)
201

Dimensions W x D x H (mm)
1335 x 1063 x 1819

Power connection
3 Phase, 400V, 50Hz,

Rated power (kw)
20.00

Current consumption (A)
3 x 29

Time to boil water 10°-90° C (min)
app. 28

Water connection
½", 1.5-6 bar, 35L/min

AutoTemp 02e Control

Standard

AutoTemp 11 Control
Option

AutoTemp 31 Control
NA

Butterfly valve
Option

Sieve plate
Option

Spray gun
Option

MultiClean
NA

Chilling
Option

Shipping Weight
251.0000kg

Shipping Width
1.635m

Shipping Height
1.500m

Shipping Length
1.250m

Shipping Cubic
3.065625000m3